


- 6 Dimensions for information only
- 5 For type approval information see protective beam
- 4 All products, product specifications & data are subject to change without notice.
- 3 Weight: 19,5 kg
- 2 VBG Installation Report 38-234200
- 1 Required frame stiffness for valid R58-03 certificate min 5700 cm<sup>4</sup>.

<div> <div>VBG GROUP</div> <div> <div>Description</div> <div>Set of EDHU Volvo/RVI H=140 (M16)</div> </div> </div>	<div>Modified Date</div> <div>2020-11-10</div>		<div>Modified by</div> <div>PA</div>	<div>Modification No.</div> <div>13140</div>	<div>Issue</div> <div>a</div>
	<div>3D Model No.</div> <div>21-729500</div>				<div>Engineer</div> <div>PA</div>
	<div>Sheet Size</div> <div>A2</div>	<div>Scale</div> <div>1 : 3</div>	<div>Projection</div> <div></div>	<div>Drafting Date</div> <div>2020-11-10</div>	<div>Drafted by</div> <div>PA</div>
	<div> <div>Stage</div> <div>Drawing No.</div> </div> <div> <div>P</div> <div>21-729300(F)</div> <div>INFO</div> </div>				
<div>This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program, this concerns both 2D &amp; 3D</div>					