



- 7 LH part drawn
RH part is mirror of LH
- 6 Total weight: 20 kg
- 5 All products, product specifications & data are subject to change without notice.
- 4 Required frame stiffness for valid R58-03 certificate min 5700 cm⁴.
- 3 VBG Installation Report 38-321500
- 2 For type approval information, see protective beam.
- 1 Dimensions for information only.

| | | | | | | | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------|------------|-------------|--------------------|------------------|-------|---------------|------------|------------|----|
| VBG GROUP | | Modified Date | 2021-04-15 | Modified by | RJ | Modification No. | 13387 | Issue | a | | |
| | | 3D Model No. | 21-746300 | | | | | | | Engineer | RJ |
| Description | | Sheet Size | A2 | Scale | 1:3 | Projection | | Drafting Date | 2021-04-14 | Drafted by | RJ |
| Set of EDSU MB H=240 | | Stage | P | Drawing No. | 21-746300 (F) INFO | | | | | | |
| <small>This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program, this concerns both 2D & 3D.</small> | | | | | | | | | | | |